

Safety Surfacing Positive Grip System

Slipping, whether in the work place, at home, or in public places, is probably the major cause of injury leading to loss of productivity, litigation and worst of all fatalities.

The provision of safe footing is given top priority by maintenance managers. Such maintenance problems should never be approached with temporary methods for the sake of expediency, or neglected only to recur another day.

Belzona® 4411 (Granogrip) is the proven safety surface providing positive grip systems which are:

- Hard Wearing
- Permanently Bonded
- Suited for Application on Most Surfaces and in Most Environments

Belzona® 4411 (Granogrip) provides a safer working environment. It is suitable for applications on:

- CONCRETE RAMPS
- LOADING DOCKS
- STEPS
- FACTORY WALKWAYS
- METAL DECKS
- TANK TOPS
- TILED FLOORS
- WOOD DECKS

The Unconventional Alternative.

Belzona Polymerics Ltd. Harrogate, HG1 4AY, England Fax: +44 (0) 1423 505967 • Tel: +44 (0) 1423 567641 E-mail: Com@Belzona.co.uk

Belzona Inc. Miami, Florida 33172, USA Fax: (305) 599-1140 • Tel: (305) 594-4994 E-mail: Belzona@Belzona.com





STEPS



LOADING DOCKS



FACTORY WALKWAYS



METAL DECKS

Printed from Belzona Electronic Library



TANK TOPS



CONCRETE RAMPS





BELZONA® 4000 SERIES MAGMA POLYMERS

Simplicity in Use

- Easily applied by brush.
- No special equipment required.



AVAILABLE IN 800 GM. (1.76 LBS.) UNIT SIZE

Safety in Use

- Solvent free.
- No harmful Volatile Organic Compounds (VOCs).
- Odorless.
- · USDA accepted.
- Special encapsulated system provides safe footing with an easy to clean surface.
- Will resist spillage from most industrial chemicals including acids, alkalis, hydrocarbons, lubricating oils and foodstuffs.

Versatility in Application

- Bonds to most rigid substrates:
 - Steel 3000 psi
 - Concrete*
 Hardwood*
 - Soft wood*
 Quarry tiles*
 - *greater than cohesive strength of substrate
- Can be applied to any contoured surface.
- Available in safety colors: red, yellow and gray.

Permanency in Service

- Will not peel or wear away like adhesive strips.
- · Bond strength greater than cohesive strength of non-metallic substrates.



BS EN ISO 9002 - 1994 Certificate No. Q/09335